

The duct humidifier NKBD-24 is a product of the AIRWIN® brand of BOGA GmbH. It is used for the fully automatic production of aerosol mist from demineralised water according to the ultrasonic principle in air treatment systems and air ducts. The humidifier is controlled by an external ON/OFF signal, or by a customer-supplied, continuous control signal.

### Specification

- Housing made of demineralised water-resistant stainless steel (shiny surface)
- Exhaust ducts made of plastic with integrated drip catchers
- Control unit with electric and water-side functional elements
- Central electrical control connection to 10-pin connector
- Ultrasonic oscillating circuit with 1.7 MHz exciter frequency with integrated fuse and temperature monitoring of the power transistors
- Power control according to pulse width modulation (PWM)
- Electrical power connection 48 VAC to lead-through terminals for wire up to 25 mm<sup>2</sup>
- Possibility to connect standard control signals, e.g. 0-10 VDC, 0-10 mA, 4-10 mA
- Possibility to connect a hygrostat – also 2-stage
- Possibility to connect a safety chain
- Solenoid valve combination for water supply and water drainage
- Water-technical connection without tools by means of hose connectors for metric hoses/pipes
- Automatic level control of the water level, dry-running protection, overheat protection, protection against overvoltage peaks, overflow protection, disconnection protection
- **AquaDrain**: integrated hygiene management for cyclical flushing of the water inlet pipe and cyclical or permanent emptying of the fluid tank according to pre-set parameters

### Technical data

Max. humidification output	14.4	kg/h
Number of transducers:	24	
Power consumption	735	VA

### Dimensions

Installation dimensions of humidifier – height x width x depth	237 x 736 x 288	mm
Hose water inlet	Ø 10	mm
Hose water overflow/discharge	Ø 14	mm
Weight	11.7	kg

### Conditions of use

Power supply	48 / 50	V / Hz
Conductivity of demineralised water	5...20	µS/cm
Ambient temperature	5...45	°C
Ambient humidity	0...90	% RH
Water temperature	5...40	°C
Water pressure	1...4	bar

### Scope of delivery

- NKBD-24 duct humidifier
- Installation and operating instructions
- Stop cock Ø 10 mm

### Product specification

Brand	AIRWIN®
Model	NKBD-24
Item No.	7900124



Rev 11/2016



**AIRWIN**  
Die Kunst der Luftbefeuchtung  
The art of humidification

